

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A method for driving a liquid crystal display device having a demultiplexer unit connected between a data driving circuit and a plurality of data lines on a liquid crystal panel, the demultiplexer unit distributing color data signals from any one of the output terminals of the data driving circuit to the plurality of the data lines on the liquid crystal panel, the method comprising:

classifying color data signals to be applied to the demultiplexer unit from the data driver circuit by colors;

consecutively providing the color data signals having a same color to the demultiplexer unit by the data driver circuit; and

consecutively providing the color data signals having a same color to the contiguous data lines by the demultiplexer unit before applying a different color signal.

2. (Original) The method of claim 1, wherein the color data signal are applied to the data lines on the liquid crystal panel in a combination of sequences of color data signals of red, green and blue.

3. (Original) The method of claim 2, wherein the color data signals are applied to the data lines on the liquid crystal panel in a sequence of red, green and blue signals.

4. (Original) The method of claim 2, wherein the color data signals are applied to the data lines on the liquid crystal panel in a sequence of green, blue and red signals.

5. (Original) The method of claim 2, wherein the color data signals are applied to the data lines on the liquid crystal panel in a sequence of blue, red and green signals.

6. (Original) The method of claim 1, wherein the classifying step includes arranging the color data signals having the same color according to a sequence of dot inversion system where each contiguous pixel of the liquid crystal panel has a reverse polarity.

7. (Original) The method of claim 1, wherein the demultiplexer unit includes a plurality of demultiplexers.

8. (Original) The method of claim 7, wherein each of the plurality of the demultiplexers is connected to at least five data lines of the liquid crystal panel.

9. (Original) The method of claim 7, wherein each of the plurality of the demultiplexers is connected to an odd number of data lines.

10. (Original) The method of claim 7, wherein each of the plurality of the demultiplexer is connected to a number of data lines in a multiple of six.

11. (Currently Amended) A liquid crystal display device comprising ~~[[having]]~~ a data driving unit, ~~[[and]]~~ a liquid crystal panel having a plurality of data lines, ~~comprising and~~ a demultiplexer unit connected between the data driving unit ~~[[circuit]]~~ and the ~~plurality of data lines on the liquid crystal panel, the demultiplexer unit and~~ distributing color data signal~~[[s]]~~ from any one of ~~output-out put~~ terminals of the data driving ~~circuit-unit~~ to the plurality of data lines on the liquid crystal~~[[panel]]~~, wherein the data driver consecutively provides the color data signals having a same color to the demultiplexer unit and the demultiplexer unit consecutively providing the color data signals having a same color to the contiguous data lines before applying a different color signal.

12. (Previously Presented) The liquid crystal display device of claim 11, wherein the color data signal are applied to the data lines on the liquid crystal panel in a combination of sequences of color data signals of red, green, and blue.

13. (Original) The liquid crystal display device of claim 12, wherein the color data signals are applied to the data lines on the liquid crystal panel in a sequence of red, green and blue signals.

14. (Original) The liquid crystal display device of claim 12, wherein the color data signals are applied to the data lines on the liquid crystal panel in a sequence of green, blue and red signals.

15. (Original) The liquid crystal display device of claim 12, wherein the color data signals are applied to the data lines on the liquid crystal panel in a sequence of blue, red and green signals.

16. (Previously Presented) The liquid crystal display device of claim 11, wherein the color data signals are applied to the demultiplexer unit having a same color according to a sequence of a dot inversion system where each contiguous pixel of the liquid crystal panel has a reverse polarity.

17. (Previously Presented) The liquid crystal display device of claim 11, wherein the demultiplexer unit includes a plurality of demultiplexers.

18. (Original) The liquid crystal display device of claim 17, wherein each of the plurality of the demultiplexers is connected to at least five data lines on the liquid crystal panel.

19. (Original) The liquid crystal display device of claim 17, wherein each of the plurality of the demultiplexers is connected to an odd number of data lines.

20. (Original) The liquid crystal display device of claim 17, wherein each of the plurality of the demultiplexer is connected to a number of data lines in a multiple of six.